
Nomex Fiber Packing With Rubber Core

Code: KXTP305



Description

Nomex fiber packing with silicone rubber core, high elastic rubber core can absorb vibration to control leakage. The core can be changed following customers requirements.



Item no.: KXTP305

Nomex Fiber Packing With Rubber Core Item no.: KXTP305

* Wear-resistant packing that is nevertheless gentle to shaft surface.

* Clean, and easy-to-install packing.

* Can will multi-rubber for those machine with severe vibration.

Typical Application

* This is a universal packing which can be used for pumps in all types of industry.

- * Designed specially for pumps, agitators, mixer,etc.
- * Excellent suitable for standardization in entire industrial sectors.

Technical Data

Material		Dupont Aramid Fiber (with or without PTFE impregnated)
Temperature Range		-100 up to +280 oC
Process	Rotating	25 bar
	Reciprocating	50 bar
	Static	100 bar
Shaft Speed		20 m/s
PH		1~13
Density		Appr. 1.3 g/cm3

Copyright © 2014-2015 Ningbo Kaxite Sealing Materials Co., Ltd. No.134,Huancheng North Road,Jiangbei District, Ningbo City,Zhejiang Province,China (Zip:315020) Website:<u>http://www.seal-china.com</u> E-mail:<u>sales@seal-china.com</u>